

# SOFTCLEAN™ DOSE

A stainless steel softwash trolley for chemical dosing.

This product can mix Algo Clear (or similar) accurately with water at a pre-set ratio on demand. Connect to a water source to produce a chemical mix either via the pump or directly through the Dosatron dosing unit. The Softclean™ Dose has receptacles for two 5ltr chemical containers.

## Features

- Durable stainless steel frame.
- Streamline® V16 flow controller to maximise flow and save wasting solution.
- Low profile flat-free tyres, for rough terrain.
- Built-in booster pump and lithium-ion battery. (5 hour run time)
- Holds two 5ltr chemical containers.
- Lightweight frame with handle mounted on the front plate for easy lifting and handling.
- Dosatron metering valve for accurate chemical dosing.

## Specification

- **Inlet Pressure Requirement:** 20psi
- **Inlet Water Flow Requirement:** 15lpm
- **Optimum Operating Pressure:** 85psi
- **Standard Water Inlet Connection:** Hoselock connection
- **Electrical Power Supply:** 12v Lithium-Ion battery
- **Minimum Operating Temperature:** 5°C
- **Maximum Operating Temperature:** 40°C
- **Water Flow (optimum output)** 15lpm
- **External Adjustable Injection Rate:** 0.15-8.75 %
- **Maximum Viscosity of concetrate:** 400cSt at 20°C

**Think you could benefit from an Softclean™ Dose System?**

Call our sales team on +44 (0) 1626 830 830

**Please Note** - Not suitable for use with Sodium Hypochloride

Weight  
KG  
16.5kg

