

Knapsack Sprayer: Routine Operator Checklist

GENERAL CONDITION

OK

- Clean
- No apparent damage
- Strap fixing points secure

Fill with water

- Will straps take weight
- Is the sprayer stable when filled

LEAKAGE CHECK

- Check for leaks, test when upright & on sides

FUNCTION CHECK

- Check pressure relief valve to max. limit
- Spray out – Is cut off valve working?
- Is spray pattern correct?
- Is nozzle undamaged
- Is nozzle flow rate within 10% of manufacturer's stated standard output?

INTERNAL RESIDUE

- Spray out fan collapses and air appears
- Is remaining liquid less than a cupful?

FOLLOWING USE

- Rinse with detergent
- Rinse twice with water – flush out through lance
- Clean nozzle and all filters in water and with a soft brush
- Clean outside of tank and strap
- Follow disposal procedure for rinsing's

MAKE SURE NO LIQUIDS ENTER ANY DRAINS

Date checked: _____

Signed: _____

Need help, or spares call Progreen 0800 032 6262

Visit www.progreen.co.uk

ProGreen.co.uk
WEED CONTROL & GROUND CARE


The Voluntary Initiative

Developed by NSTS and the Crop Protection Association as Part of the Voluntary Initiative

www.amenity.org.uk

www.voluntaryinitiative.org.uk

www.nsts.org.uk